WiFi 7 (802.11BE) 2×2 MU-MIMO 6 GHz High Power Single Band Wireless Module



Model: WLWE7002E6-27

KEY FEATURES

- Qualcomm QCN9274-I 'Waikiki' series for Industrial Grade
- 6GHz, 2×2 MU-MIMO, up to 5764 Mbps physical data rate
- Single Band 6G 2x2 WiFi 7 (802.11be)
- MiniPCIe Interface with PCIe 3.0
- Based on WK01.6 reference design
- Supports up to 4096-QAM
- -20°C to 70°C operating temperature*

**For industrial-grade environmental temperature requirements, please contact our sales representative for a customized heatsink solution.*

Specifications

Chipset	Qualcomm QCN9274-I 'Waikiki' series for Industrial grade
System Memory	2Mbit serial I²C bus EEPROM
Reference Design	WK01.6
Host Interface	MiniPCIe Interface with PCIe 3.0
Operating Voltage	3.3V 5V
Power Consumption	8.8W (Max)
Wireless	6GHz 802.11ax/be, max 26dBm per chain 2x MMCX Connectors
Frequency Range	5.925~7.125GHz
Modulation Techniques	OFDMA: BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM,1024-QAM, 4096-QAM
Channel Spectrum Widths for WLAN	Supports 20/40/80/160/320MHz at 6GHz
Operating Systems	Linux
Certification	REACH & RoHS Compliance
Environmental Temperature [1]	Operating temperature: -20°C to 70°C, Storage: -40°C to 90°C
Environmental Humidity, Non-Condensing	Operating: 5% to 95%, Storage: Max. 90%
Dimensions (W x H x D) in mm	57 X 62.7 X 14.2 mm

COMPEX SYSTEMS PRELIMINERY

**Configurations are subject to change without notifications.*
***Can be requested from respective sales executive.*

[1] For industrial-grade environmental temperature requirements, please contact our sales representative for a customized heatsink solution.

Copyright © Compex Systems. All rights reserved. COMPEX and the COMPEX logo, are registered trademarks of Compex Systems Pte Ltd.
While every effort is made to ensure the information is accurate, Compex does not accept liability for any errors or mistakes that may arise.
All specifications are subject to change without notice.

Compex Systems Pte Ltd | www.compex.com.sg | (+65) 6286 2086 | sales@compex.com.sg | Last Update: 11/09/2026
Prepared by: JC | Checked by: LL HJ GS HM

RF Performance Table at 6GHz

	Data Rate	TX Power (per chain)	TX Power (2 chains)	Tolerance
6GHz 802.11be EHT20	MCS 0	26dBm	29dBm	±2dB
	MCS 1	26dBm	29dBm	±2dB
	MCS 2	25dBm	28dBm	±2dB
	MCS 3	24dBm	27dBm	±2dB
	MCS 4	23dBm	26dBm	±2dB
	MCS 5	23dBm	26dBm	±2dB
	MCS 6	22dBm	25dBm	±2dB
	MCS 7	22dBm	25dBm	±2dB
	MCS 8	21dBm	24dBm	±2dB
	MCS 9	21dBm	24dBm	±2dB
	MCS 10	20dBm	23dBm	±2dB
	MCS 11	20dBm	23dBm	±2dB
	MCS 12	19dBm	22dBm	±2dB
	MCS 13	19dBm	22dBm	±2dB
6GHz 802.11be EHT40	MCS 0	26dBm	29dBm	±2dB
	MCS 1	26dBm	29dBm	±2dB
	MCS 2	25dBm	28dBm	±2dB
	MCS 3	24dBm	27dBm	±2dB
	MCS 4	23dBm	26dBm	±2dB
	MCS 5	23dBm	26dBm	±2dB
	MCS 6	22dBm	25dBm	±2dB
	MCS 7	22dBm	25dBm	±2dB
	MCS 8	21dBm	24dBm	±2dB
	MCS 9	21dBm	24dBm	±2dB
	MCS 10	20dBm	23dBm	±2dB
	MCS 11	20dBm	23dBm	±2dB
	MCS 12	19dBm	22dBm	±2dB
	MCS 13	19dBm	22dBm	±2dB
6GHz 802.11be EHT80	MCS 0	26dBm	29dBm	±2dB
	MCS 1	26dBm	29dBm	±2dB
	MCS 2	25dBm	28dBm	±2dB
	MCS 3	24dBm	27dBm	±2dB
	MCS 4	23dBm	26dBm	±2dB
	MCS 5	23dBm	26dBm	±2dB
	MCS 6	22dBm	25dBm	±2dB
	MCS 7	22dBm	25dBm	±2dB
	MCS 8	21dBm	24dBm	±2dB
	MCS 9	21dBm	24dBm	±2dB
	MCS 10	20dBm	23dBm	±2dB
	MCS 11	20dBm	23dBm	±2dB
	MCS 12	19dBm	22dBm	±2dB
	MCS 13	19dBm	22dBm	±2dB

	Data Rate	RX Specifications Sensitivity	Tolerance
6GHz 802.11be EHT20	MCS 0	-94dBm	±2dB
	MCS 1	-92dBm	±2dB
	MCS 2	-89dBm	±2dB
	MCS 3	-86dBm	±2dB
	MCS 4	-83dBm	±2dB
	MCS 5	-80dBm	±2dB
	MCS 6	-77dBm	±2dB
	MCS 7	-76dBm	±2dB
	MCS 8	-72dBm	±2dB
	MCS 9	-70dBm	±2dB
	MCS 10	-66dBm	±2dB
	MCS 11	-65dBm	±2dB
	MCS 12	-61dBm	±2dB
	MCS 13	-58dBm	±2dB
6GHz 802.11be EHT40	MCS 0	-91dBm	±2dB
	MCS 1	-89dBm	±2dB
	MCS 2	-86dBm	±2dB
	MCS 3	-83dBm	±2dB
	MCS 4	-80dBm	±2dB
	MCS 5	-76dBm	±2dB
	MCS 6	-75dBm	±2dB
	MCS 7	-74dBm	±2dB
	MCS 8	-70dBm	±2dB
	MCS 9	-68dBm	±2dB
	MCS 10	-65dBm	±2dB
	MCS 11	-62dBm	±2dB
	MCS 12	-59dBm	±2dB
	MCS 13	-57dBm	±2dB
6GHz 802.11be EHT80	MCS 0	-88dBm	±2dB
	MCS 1	-86dBm	±2dB
	MCS 2	-84dBm	±2dB
	MCS 3	-81dBm	±2dB
	MCS 4	-78dBm	±2dB
	MCS 5	-73dBm	±2dB
	MCS 6	-72dBm	±2dB
	MCS 7	-70dBm	±2dB
	MCS 8	-67dBm	±2dB
	MCS 9	-64dBm	±2dB
	MCS 10	-61dBm	±2dB
	MCS 11	-60dBm	±2dB
	MCS 12	-57dBm	±2dB
	MCS 13	-55dBm	±2dB

COMPEX SYSTEMS PRELIMINERY

Copyright © Compex Systems. All rights reserved. COMPEX and the COMPEX logo, are registered trademarks of Compex Systems Pte Ltd.
While every effort is made to ensure the information is accurate, Compex does not accept liability for any errors or mistakes that may arise.
All specifications are subject to change without notice.

RF Performance Table at 6GHz

	Data Rate	TX Power (per chain)	TX Power (2 chains)	Tolerance
6GHz 802.11be EHT160	MCS 0	26dBm	29dBm	±2dB
	MCS 1	26dBm	29dBm	±2dB
	MCS 2	25dBm	28dBm	±2dB
	MCS 3	24dBm	27dBm	±2dB
	MCS 4	23dBm	26dBm	±2dB
	MCS 5	23dBm	26dBm	±2dB
	MCS 6	22dBm	25dBm	±2dB
	MCS 7	22dBm	25dBm	±2dB
	MCS 8	21dBm	24dBm	±2dB
	MCS 9	21dBm	24dBm	±2dB
	MCS 10	20dBm	23dBm	±2dB
	MCS 11	20dBm	23dBm	±2dB
	MCS 12	19dBm	22dBm	±2dB
	MCS 13	19dBm	22dBm	±2dB
6GHz 802.11be EHT320	MCS 0	26dBm	29dBm	±2dB
	MCS 1	26dBm	29dBm	±2dB
	MCS 2	25dBm	28dBm	±2dB
	MCS 3	24dBm	27dBm	±2dB
	MCS 4	23dBm	26dBm	±2dB
	MCS 5	23dBm	26dBm	±2dB
	MCS 6	22dBm	25dBm	±2dB
	MCS 7	22dBm	25dBm	±2dB
	MCS 8	21dBm	24dBm	±2dB
	MCS 9	21dBm	24dBm	±2dB
	MCS 10	20dBm	23dBm	±2dB
	MCS 11	20dBm	23dBm	±2dB
	MCS 12	19dBm	22dBm	±2dB
	MCS 13	19dBm	22dBm	±2dB

	Data Rate	RX Specifications Sensitivity	Tolerance
6GHz 802.11be EHT160	MCS 0	-86dBm	±2dB
	MCS 1	-83dBm	±2dB
	MCS 2	-81dBm	±2dB
	MCS 3	-78dBm	±2dB
	MCS 4	-75dBm	±2dB
	MCS 5	-71dBm	±2dB
	MCS 6	-70dBm	±2dB
	MCS 7	-68dBm	±2dB
	MCS 8	-65dBm	±2dB
	MCS 9	-63dBm	±2dB
	MCS 10	-59dBm	±2dB
	MCS 11	-57dBm	±2dB
	MCS 12	-55dBm	±2dB
	MCS 13	-53dBm	±2dB
6GHz 802.11be EHT320	MCS 0	-82dBm	±2dB
	MCS 1	-80dBm	±2dB
	MCS 2	-78dBm	±2dB
	MCS 3	-74dBm	±2dB
	MCS 4	-71dBm	±2dB
	MCS 5	-67dBm	±2dB
	MCS 6	-66dBm	±2dB
	MCS 7	-65dBm	±2dB
	MCS 8	-62dBm	±2dB
	MCS 9	-60dBm	±2dB
	MCS 10	-55dBm	±2dB
	MCS 11	-53dBm	±2dB
	MCS 12	-52dBm	±2dB
	MCS 13	-51dBm	±2dB

COMPEX SYSTEMS PRELIMINARY

Copyright © Compex Systems. All rights reserved. COMPEX and the COMPEX logo, are registered trademarks of Compex Systems Pte Ltd.
While every effort is made to ensure the information is accurate, Compex does not accept liability for any errors or mistakes that may arise.
All specifications are subject to change without notice.


Component Map




COMPEX SYSTEMS
PRELIMINERY


Copyright © Compex Systems. All rights reserved. COMPEX and the COMPEX logo, are registered trademarks of Compex Systems Pte Ltd.
While every effort is made to ensure the information is accurate, Compex does not accept liability for any errors or mistakes that may arise.
All specifications are subject to change without notice.

Mechanical Dimensions



COMPEX SYSTEMS
PRELIMINERY





All dimensions are in mm

Copyright © Compex Systems. All rights reserved. COMPEX and the COMPEX logo, are registered trademarks of Compex Systems Pte Ltd.
While every effort is made to ensure the information is accurate, Compex does not accept liability for any errors or mistakes that may arise.
All specifications are subject to change without notice.

Ordering Configuration

Item Code	Model	Description
WLWE7002E6-27 7B000NX-TE	WLWE7002E6-27-I	QCN9274-I 2x2 802.11ax/be Support 6GHz High Power Single Band MiniPCIe interface with PCIe 3.0 Module

COMPEX SYSTEMS PRELIMINERY

Copyright © Compex Systems. All rights reserved. COMPEX and the COMPEX logo, are registered trademarks of Compex Systems Pte Ltd.
While every effort is made to ensure the information is accurate, Compex does not accept liability for any errors or mistakes that may arise.
All specifications are subject to change without notice.

Compex Systems Pte Ltd | www.compex.com.sg | (+65) 6286 2086 | sales@compex.com.sg | Last Update: 11/09/2026
Prepared by: JC | Checked by: LL HJ GS HM

Chipsets Comparisons

		QCN6224	QCN6274	QCN9274
Band Operation	4 Single Band	✓	✓	✓
	2+2 Dual Band	✓	✓	✓
	2.4GHz	✓	✓	✓
	4.9GHz	-	-	✓
	5GHz	✓	✓	✓
	6GHz	-	✓	✓
	Channel Support	Up to 160MHz at 5GHz	Up to 320MHz at 6GHz	Up to 320MHz at 6GHz
Performance	4K QAM	✓	✓	✓
	#clients	128	256	512
	#OFDMA users	8	16	37
	DL OFDMA + TxBF	-	✓	✓
	DL/UL MU-MIMO	✓	✓	✓
Advanced 11be Features	WFA certified MLO	✓	✓	✓
	Puncture	Static	Static	Static & Dynamic
Others	DPD	✓	✓	✓
	FIPS	-	-	✓
Software Packages	Provisioned Multi Link	✓	✓	✓
	Dense Deployment	✓	✓	✓
	Location & RF Sensing	✓	✓	✓

COMPEX SYSTEMS PRELIMINERY

Copyright © Compex Systems. All rights reserved. COMPEX and the COMPEX logo, are registered trademarks of Compex Systems Pte Ltd.
While every effort is made to ensure the information is accurate, Compex does not accept liability for any errors or mistakes that may arise.
All specifications are subject to change without notice.